


Silicon Epitaxial Planar Transistor

2SD1819A

FEATURES

- Low collector to emitter saturation voltage.
- High forward current transfer ratio h_{FE} .
- Complementary to 2SB1218A.
- Small package.



APPLICATIONS

- For general amplification.

ORDERING INFORMATION

Type No.	Marking	Package Code
2SD1819A	ZQ/ZR/ZS	SOT-323

MAXIMUM RATING @ $T_a=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	60	V
V_{CEO}	Collector-Emitter Voltage	50	V
V_{EBO}	Emitter-Base Voltage	7	V
I_C	Collector Current -Continuous	100	mA
P_C	Collector Dissipation	150	mW
T_j, T_{stg}	Junction and Storage Temperature	-55~150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified

Silicon Epitaxial Planar Transistor


2SD1819A

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=10\mu A, I_E=0$	60			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=2mA, I_B=0$	50			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu A, I_C=0$	7			V
Collector cut-off current	I_{CBO}	$V_{CB}=20V, I_E=0$			0.1	μA
Collector cut-off current	I_{CEO}	$V_{EB}=10V, I_B=0$			0.1	μA
DC current gain	h_{FE}	$V_{CE}=10V, I_C=2mA$ $V_{CE}=2V, I_C=100mA$	160 90		460	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=100mA, I_B=10mA$		0.1	0.3	V
Transition frequency	f_T	$V_{CB}=10V, I_E=-2mA, f=200MHz$		150		MHz
Collector output capacitance	C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$		3.5		pF

CLASSIFICATION OF h_{FE}






Range	160-260	210-340	290-460
Marking	ZQ	ZR	ZS

TYPICAL CHARACTERISTICS @ $T_a=25^\circ C$ unless otherwise specified



Silicon Epitaxial Planar Transistor


2SD1819A



PACKAGE OUTLINE

Plastic surface mounted package


SOT-323



Silicon Epitaxial Planar Transistor

2SD1819A

SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
2SD1819A	SOT-323	3000/Tape&Reel

www.s-manuals.com