

P-Channel 200-V (D-S) MOSFET

PRODUCT SUMMARY			
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)	Q_g (Typ)
-200	5.0 @ $V_{GS} = -10$ V	-0.38	4.1
	5.1 @ $V_{GS} = -6$ V	-0.37	

FEATURES


- TrenchFET® Power MOSFETS
- Small, Thermally Enhanced SC-70 Package
- Ultra Low On-Resistance




Pb-free
Available

APPLICATIONS


- Active Clamp Switch in DC/DC Power Supplies



Top View



Ordering Information: Si1419DH-T1—E3



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)					
Parameter	Symbol	5 secs	Steady State	Unit	
Drain-Source Voltage	V_{DS}	-200		V	
Gate-Source Voltage	V_{GS}	± 20			
Continuous Drain Current ($T_J = 150^\circ\text{C}$) ^a	I_D	$T_A = 25^\circ\text{C}$	-0.38	-0.3	A
		$T_A = 85^\circ\text{C}$	-0.27	-0.22	
Pulsed Drain Current	I_{DM}	-0.5			
Continuous Diode Current (Diode Conduction) ^a	I_S	-1.3	-0.83		
Single Pulse Avalanche Current	$L = 0.1$ mH	I_{AS}	-1.9		
Single Pulse Avalanche Energy		E_{AS}	0.18		mJ
Maximum Power Dissipation ^a	P_D	$T_A = 25^\circ\text{C}$	1.56	1.0	W
		$T_A = 85^\circ\text{C}$	0.81	0.52	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150		$^\circ\text{C}$	

THERMAL RESISTANCE RATINGS					
Parameter	Symbol	Typical	Maximum	Unit	
Maximum Junction-to-Ambient ^a	R_{thJA}	$t \leq 5$ sec	60	80	$^\circ\text{C/W}$
		Steady State	100	125	
Maximum Junction-to-Foot (Drain)	R_{thJF}	34	45		

Notes

a. Surface Mounted on 1" x 1" FR4 Board.



SPECIFICATIONS (T_J = 25 °C UNLESS OTHERWISE NOTED)



Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -100 μA	-2.5		-4.5	V
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -200 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -200 V, V _{GS} = 0 V, T _J = 85 °C			-5	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = -15 V, V _{GS} = -10 V	-0.5			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = -10 V, I _D = -0.4 A		3.98	5.0	Ω
		V _{GS} = -6 V, I _D = -0.4 A		4.06	5.1	
Forward Transconductance ^a	g _{fs}	V _{DS} = -10 V, I _D = -0.4 A		1.0		S
Diode Forward Voltage ^a	V _{SD}	I _S = -0.4 A, V _{GS} = 0 V		-0.80	-1.1	V
Dynamic^b						
Total Gate Charge	Q _g	V _{DS} = -100 V, V _{GS} = -10 V, I _D = -0.4 A		4.1	6.2	nC
Gate-Source Charge	Q _{gs}			0.8		
Gate-Drain Charge	Q _{gd}			1.3		
Gate Resistance	R _g	f = 1.0 MHz		17		Ω
Turn-On Delay Time	t _{d(on)}	V _{DD} = -100 V, R _L = 100 Ω I _D ≅ -1 A, V _{GEN} = -4.5 V, R _g = 6 Ω		6	9	ns
Rise Time	t _r			12	18	
Turn-Off Delay Time	t _{d(off)}			12	18	
Fall Time	t _f			12	18	
Reverse Recovery Time	t _{rr}	I _F = -0.4 A, di/dt = 100 A/μs		55	83	ns
Body Diode Reverse Recovery Charge	Q _{rr}			130	200	

Notes







- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)







TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)






TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)





TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73241>.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

www.s-manuals.com