



# SP6853

## Green-Mode PWM Controller

### DESCRIPTION

The SP6853 is a low cost , low startup current , current mode PWM controller with green-mode power-saving operation. The integrated functions include the leading-edge blanking of the current sensing, internal slope compensation. It would provide the users a superior AC/DC power application of higher efficiency, low external component counts, and lower cost solution for applications.

The SP6853 features more protections or functions for the following characteristics :

※Add OLP (Over Load Protection) function to provide better protection performance for fault conditions like short circuit or over load.

※Modify the OVP (Over Voltage Protection) mechanism from the cycle-by-cycle mode to the hiccup mode.

SP6853 is available by SOT-23-6L / DIP-8P packages.

### FEATURES


- High-Voltage BiCMOS Process
- Very Low Startup Current (<20μA)
- Under Voltage Lockout (UVLO )
- Current Mode Control
- Non-audible-noise Green Mode Control
- Current Limiting
- LEB (Leading-Edge Blanking) on CS Pin
- OLP (Over Load Protection)
- OVP (Over Voltage Protection) on Vcc Pin
- Leading-Edge Blanking
- Programmable Switching Frequency
- Internal Slope Compensation
- Green-Mode Control for Power Saving
- 300mA Driving Capability
- 

### APPLICATIONS


- AC/DC Switching Power Adaptor
- Battery Charger
- PC 5V Standby Power.
- Open-Frame Switching Power Supply

### PIN CONFIGURATION

#### SOT-23-6L




#### DIP-8P



### PART MARKING

#### SOT-23-6L




#### DIP-8P






# SP6853 Green-Mode PWM Controller

## TYPICAL APPLICATION CIRCUIT



## TYPICAL APPLICATION CIRCUIT ( High Efficiency SMPS + Synchronous Rectifier )





# SP6853

## Green-Mode PWM Controller

### PIN DESCRIPTION


#### SP6853D8TG

Pin	Symbol	Description
1	OUT	Gate driver output to drive the external MOSFET
2	VCC	Supply Voltage in
3	NC	Unconnected pin
4	CS	Current sense. This pin senses the voltage across a resistor, to control PWM output. This pin also provides current amplitude information for current-mode control.
5	RT	This current is used to charge an internal capacitor, to determine the switching frequency.
6	NC	Unconnected pin
7	COMP	Voltage feedback. The pin provides the output voltage regulation signal., it provides feedback to the internal PWM comparator, so that the PWM comparator can control the duty cycle.
8	GND	Ground

#### SP6853S26RG

Pin	Symbol	Description
1	GND	Ground
2	COMP	Voltage feedback. The pin provides the output voltage regulation signal., it provides feedback to the internal PWM comparator, so that the PWM comparator can control the duty cycle
3	RT	This current is used to charge an internal capacitor, to determine the switching frequency.
4	CS	Current sense. This pin senses the voltage across a resistor, to control PWM output. This pin also provides current amplitude information for current-mode control
5	VCC	Supply Voltage in
6	OUT	Gate driver output to drive the external MOSFET

### BLOCK DIAGRAM





# SP6853

## Green-Mode PWM Controller

### ORDERING INFORMATION

Part Number	Package	Part Marking
SP6853D8TGB	DIP-8P	SP6853I
SP6853S26RGB	SOT-23-6L	853YW

※ SP6853D8TG : Tube ; Pb – Free ; Halogen-Free

※ SP6853S26RG : Tape Reel ; Pb – Free ; Halogen-Free

### ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub>=25°C, unless otherwise specified.)

The following ratings designate persistent limits beyond which damage to the device may occur.

Symbol	Parameter	Value	Unit
V <sub>CC</sub>	DC Supply Voltage	36	V
V <sub>COMP/RT/CS</sub>	COMP / RT / CS Voltage	-0.3 ~ 7.0	V
P <sub>D</sub>	Power Dissipation @ T <sub>A</sub> =85°C (*)	0.3	W
ESD	Human Body Model	4	KV
	Machine Model	300	V
T <sub>ope</sub>	Operating Ambient Temperature	-40 ~ 85	°C
T <sub>J</sub>	Operating Junction Temperature Range	-40 ~ 150	°C
T <sub>STG</sub>	Storage Temperature Range	-40 ~ 150	°C
T <sub>LEAD</sub>	Pb-Free Lead Soldering Temperature for 5 sec.	260	°C
R <sub>θJC</sub>	Thermal Resistance Junction – Case (*)	SOT-23-6L	210
		DIP-8P	95

(\*) The power dissipation and thermal resistance are evaluated under copper board mounted with free air conditions.



# SP6853

## Green-Mode PWM Controller

### ELECTRICAL CHARACTERISTICS

( $T_A=25^{\circ}\text{C}$ ,  $V_{CC}=15\text{V}$ , unless otherwise specified.)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
<b>Supply Voltage ( Vcc Pin )</b>						
I <sub>stt</sub>	Startup Current			10	20	uA
I <sub>op</sub>	Operating Current	V <sub>COMP</sub> = 0V		2.7	4	mA
		V <sub>COMP</sub> = 3V		2.4		mA
		Protection tripped (OLP, OVP)		1.0		mA
UVLO (off)	Min. Operating Voltage		9.0	10.0	11.0	V
UVLO (on)	Start Threshold Voltage		15.0	16.0	17.0	V
OVP Level	Over Voltage Protection		24	26	29.5	V
<b>Voltage Feedback ( Comp Pin )</b>						
I <sub>sc</sub>	Short Circuit Current			1.25	2.2	mA
V <sub>op</sub>	Open Loop Voltage			6		V
V <sub>TH(GM)</sub>	Green Mode Threshold V <sub>COMP</sub>			2.35		V
<b>Oscillator ( RT Pin )</b>						
F <sub>osc</sub>	Frequency	R <sub>T</sub> =100K $\Omega$	60.0	68.0	75.0	KHz
F <sub>osc(GM)</sub>	Green Mode Frequency	F <sub>s</sub> =65.0KHz		22		KHz
F <sub>dt</sub>	Frequency Variation versus Temp. Deviation	(-40 $^{\circ}\text{C}$ ~105 $^{\circ}\text{C}$ )			3	%
F <sub>dv</sub>	Frequency Variation versus V <sub>CC</sub> Deviation	(V <sub>CC</sub> =11V-25V)			1	%
<b>Current Sensing ( CS Pin )</b>						
V <sub>cs(off)</sub>	Maximum Input Voltage		0.8	0.85	0.9	V
T <sub>LEDD</sub>	Leading Edge Blanking Time			280		nS
Z <sub>cs</sub>	Input impedance		1			M $\Omega$
T <sub>PD</sub>	Delay to Output			100		nS
<b>Gate Driver Output ( OUT Pin )</b>						
DC (Max)	Maximum Duty Cycle		70	75	80	%
DC (Min)	Minimum Duty Cycle			0		%
V <sub>OL</sub>	Output Low Level	V <sub>CC</sub> =15V, I <sub>o</sub> =20mA			1	V
V <sub>OH</sub>	Output High Level	V <sub>CC</sub> =15V, I <sub>o</sub> =20mA	8			V
T <sub>r</sub>	Rising Time	Load Cap=1000pF		50	200	nS
T <sub>f</sub>	Falling Time	Load Cap=1000pF		30	120	nS
<b>OLP ( Over Load Protection )</b>						
T <sub>LOLP</sub>	OLP Trip Level			5.0		V
T <sub>DOLP</sub>	OLP Delay Time (note)			60		mS

Note: The OLP delay time is proportional to the period of switching cycle. So that, the lower RT value will set the higher switching frequency and the shorter OLP delay time.



# SP6853 Green-Mode PWM Controller

PERFORMANCE CHARACTERISTICS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified.)




Fig. 1 UVLO (on) vs. Temperature




Fig. 2 UVLO (off) vs. Temperature




Fig. 3 Frequency vs. Temperature




Fig. 4 Green Mode Frequency vs. Temperature




Fig. 5 Frequency vs. Vcc




Fig. 6 Green Mode Frequency vs. Vcc



# SP6853 Green-Mode PWM Controller

PERFORMANCE CHARACTERISTICS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified.)




Fig. 7 Max Duty vs. Temperature




Fig. 8  $V_{CS(off)}$  vs. Temperature




Fig. 9 Startup Current ( $I_{startup}$ ) vs. Temperature




Fig. 10 VCC OVP vs. Temperature




Fig. 11  $V_{comp}$  open loop voltage vs. Temperature





Fig. 12 OLP-Trip Level vs. Temperature




# SP6853 Green-Mode PWM Controller


PERFORMANCE CHARACTERISTICS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified.)




Max Duty Cycle




Min Duty Cycle




Max Duty Cycle



Min Duty Cycle



Max Duty Cycle




Min Duty Cycle






# SP6853 Green-Mode PWM Controller


PERFORMANCE CHARACTERISTICS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified.)




Rising Time Load




Falling Time Load




Rising Time Load



Falling Time Load



Rising Time Load




Falling Time Load




# SP6853 Green-Mode PWM Controller


PERFORMANCE CHARACTERISTICS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified.)




Leading Edge Blanking Time




OLP Delay Time




Leading Edge Blanking Time



OLP Delay Time



Leading Edge Blanking Time




OLP Delay Time



# SP6853

## Green-Mode PWM Controller

### DIP- 8P PACKAGE OUTLINE




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.710	4.310	0.146	0.170
A1	0.510		0.020	
A2	3.200	3.600	0.126	0.142
B	0.380	0.570	0.015	0.022
B1	1.524 (BSC)		0.060 (BSC)	
C	0.204	0.360	0.008	0.014
D	9.000	9.400	0.354	0.370
E	6.200	6.600	0.244	0.260
E1	7.320	7.920	0.288	0.312
e	2.540 (BSC)		0.100 (BSC)	
L	3.000	3.600	0.118	0.142
E2	8.400	9.000	0.331	0.354



# SP6853

## Green-Mode PWM Controller

### SOT-23-6L PACKAGE OUTLINE



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.400	0.012	0.016
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.700REF		0.028REF	
L1	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°



# SP6853

## Green-Mode PWM Controller

---

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties that may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation

©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan, 115, R.O.C

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

<http://www.syncpower.com>

[www.s-manuals.com](http://www.s-manuals.com)